



Leading Through Innovation

HSS & HSS-E

YG TAP GENERAL

YG Gewindebohrer Universal

- Suitable for Tapping Blind / Through Holes due to Flute Geometry and Excellent Chip Evacuation
- Geeignet für das Gewindeschneiden von Grund- und Durchgangsbohrungen aufgrund der Nutengeometrie und der hervorragenden Spanabfuhr

SELECTION GUIDE



HSS & HSS-E
YG TAP
GENERAL

Suitable for Tapping Blind / Through Holes
due to Flute Geometry and Excellent Chip Evacuation

Please visit globalyg1.com/mat for material search

◎ : Excellent ○ : Good

Recommended cutting conditions : p.B309

ISO	VDI 3323	Material Description	Composition / Structure / Heat Treatment		HB	HRc			
P	1	Non-alloy steel	About 0.15% C	Annealed	125		○	○	○
	2		About 0.45% C	Annealed	190	13	◎	◎	◎
	3		About 0.45% C	Quenched & Tempered	250	25	◎	◎	◎
	4		About 0.75% C	Annealed	270	28	◎	◎	◎
	5		About 0.75% C	Quenched & Tempered	300	32	○	○	○
	6	Low alloy steel		Annealed	180	10	◎	◎	◎
	7			Quenched & Tempered	275	29	◎	◎	◎
	8			Quenched & Tempered	300	32	○	○	○
	9			Quenched & Tempered	350	38			
	10	High alloyed steel, and tool steel		Annealed	200	15			
	11			Quenched & Tempered	325	35			
M	12	Stainless steel	Ferritic / Martensitic	Annealed	200	15	○	○	○
	13		Martensitic	Quenched & Tempered	240	23	○	○	○
	14		Austenitic		180	10			
	15	Grey cast iron	Pearlitic / ferritic		180	10			
K	16		Pearlitic (Martensitic)		260	26			
	17	Nodular cast iron	Ferritic		160	3	◎	◎	◎
	18		Pearlitic		250	25	◎	◎	◎
	19	Malleable cast iron	Ferritic		130				
	20		Pearlitic		230	21			
N	21	Aluminum-wrought alloy	Not Curable		60		○	○	○
	22		Curable	Hardened	100				
	23	Aluminum-cast, alloyed	≤ 12% Si, Not Curable		75		○	○	○
	24		≤ 12% Si, Curable	Hardened	90		○	○	○
	25		> 12% Si, Not Curable		130		◎	◎	◎
	26	Copper and Copper Alloys	Cutting Alloys, PB>1%		110		○	○	○
	27		CuZn, CuSnZn (Brass)		90				
	28	Non Metallic Materials	CuSn, lead-free copper and electrolytic copper		100		◎	◎	◎
	29		Duroplastic, Fiber Reinforced Plastic						
	30		Rubber, Wood, etc.						
S	31	Heat Resistant Super Alloys	Fe Based	Annealed	200	15			
	32			Cured	280	30			
	33			Annealed	250	25			
	34		Ni or Co Based	Cured	350	38			
	35			Cast	320	34			
	36	Titanium Alloys	Pure Titanium		400 Rm				
	37		Alpha + Beta Alloys	Hardened	1050 Rm				
H	38	Hardened steel		Hardened	550	55			
	39			Hardened	630	60			
	40	Chilled Cast Iron		Cast	400	42			
	41	Hardened Cast Iron		Hardened	550	55			

Max. 3.0xD Through Hole						Max. 2.0xD Blind/Through Hole
HSS-E						
B	B	B	B	C	C	
Spiral Point	Spiral Point	Spiral Point	Spiral Point	Spiral Flute	Straight Flute	
-	-	-	-	L20	-	
TC127 (p.B283)	TD127 (p.B284)	TC227 (p.B293)	TD227 (p.B294)	TC211 (p.B295)	TC463 (p.B296)	M
TC122 (p.B285)						
TC222 (p.B286)	TD222 (p.B288)				TC473 (p.B297)	MF
TC214 (p.B290)					TC424 (p.B298)	UNC
TC234 (p.B291)						UNF
TC224 (p.B292)						BSW
						G(BSP)
						EG-M
						EG-UNC
						EG-UNF
Bright	TIN	Bright	TIN	Bright	Bright	
○	○	○	○	○	○	1
◎	◎	◎	◎	◎	◎	2
◎	◎	◎	◎	◎	○	3
◎	◎	◎	◎	◎	○	4
○	○	○	○	○	○	5
◎	◎	◎	◎	◎	○	6
◎	◎	◎	◎	◎	○	7
○	○	○	○	○	○	8
						9
						10
						11
○	○	○	○	○	○	12
○	○	○	○	○	○	13
						14
					○	15
					○	16
◎	◎	◎	◎	◎	○	17
◎	◎	◎	◎	◎	○	18
						19
						20
○	○	○	○	○		21
						22
○	○	○	○	○		23
○	○	○	○	○		24
◎	◎	◎	◎	◎		25
○	○	○	○	○	○	26
◎	◎	◎	◎	◎	○	27
						28
						29
						30
						31
						32
						33
						34
						35
						36
						37
						38
						39
						40
						41

SELECTION GUIDE



HSS & HSS-E
YG TAP
GENERAL

Suitable for Tapping Blind / Through Holes
due to Flute Geometry and Excellent Chip Evacuation




Please visit
globalyg1.com/mat
for material search

◎ : Excellent ○ : Good

Recommended cutting conditions : p.B309

ISO	VDI 3323	Material Description	Composition / Structure / Heat Treatment		HB	HRc		
P	1	Non-alloy steel	About 0.15% C	Annealed	125		○	
	2		About 0.45% C	Annealed	190	13	○	○
	3		About 0.45% C	Quenched & tempered	250	25	○	○
	4		About 0.75% C	Annealed	270	28	○	○
	5		About 0.75% C	Quenched & tempered	300	32		
	6	Low alloy steel		Annealed	180	10	○	○
	7			Quenched & tempered	275	29	○	○
	8			Quenched & tempered	300	32		
	9			Quenched & tempered	350	38		
	10	High alloyed steel, and tool steel		Annealed	200	15		
	11			Quenched & Tempered	325	35		
M	12	Stainless steel	Ferritic / Martensitic	Annealed	200	15		
	13		Martensitic	Quenched & Tempered	240	23		
	14		Austenitic		180	10		
K	15	Grey cast iron	Pearlitic / ferritic		180	10		
	16		Pearlitic (Martensitic)		260	26		
	17	Nodular cast iron	Ferritic		160	3	○	○
	18		Pearlitic		250	25	○	○
	19	Malleable cast iron	Ferritic		130			
	20		Pearlitic		230	21		
N	21	Aluminum-wrought alloy	Not Curable		60			
	22		Curable	Hardened	100			
	23	Aluminum-cast, alloyed	≤ 12% Si, Not Curable		75			
	24		≤ 12% Si, Curable	Hardened	90			
	25		> 12% Si, Not Curable		130		○	○
	26	Copper and Copper Alloys (Bronze / Brass)	Cutting Alloys, PB>1%		110		○	○
	27		CuZn, CuSnZn (Brass)		90		○	○
	28	Non Metallic Materials	CuSn, lead-free copper and electrolytic copper		100			
	29		Duroplastic, Fiber Reinforced Plastic					
	30		Rubber, Wood, etc.					
S	31	Heat Resistant Super Alloys	Fe Based	Annealed	200	15		
	32			Cured	280	30		
	33		Ni or Co Based	Annealed	250	25		
	34			Cured	350	38		
	35			Cast	320	34		
	36	Titanium Alloys	Pure Titanium		400 Rm			
	37		Alpha + Beta Alloys	Hardened	1050 Rm			
H	38	Hardened steel		Hardened	550	55		
	39			Hardened	630	60		
	40	Chilled Cast Iron		Cast	400	42		
	41	Hardened Cast Iron		Hardened	550	55		



HSS				HSS-E		
I / II / III	I / III	I / II / III	I / II / III	I / II / III	I / II / III	
Straight Flute	Straight Flute	Straight Flute	Straight Flute	Straight Flute	Straight Flute	
-	-	-	Left Hand Cut	-	-	
						M
			T7343 (p.B306)	TB373 (p.B307)	TC353 (p.B308)	
						MF
						UNC
T7363 (p.B303)						UNF
	T7509 (p.B304)					BSW
		T7609 (p.B305)				G(BSP)
						EG-M
						EG-UNC
						EG-UNF
Bright	Bright	Bright	Bright	VAP	Bright	
○	○	○	○	○	○	1
○	○	○	○	○	○	2
○	○	○	○	○	○	3
○	○	○	○	○	○	4
○	○	○	○	○	○	5
○	○	○	○	○	○	6
○	○	○	○	○	○	7
						8
						9
						10
						11
				○		12
				○		13
				○		14
						15
○	○	○	○			16
○	○	○	○			17
○	○	○	○			18
						19
						20
						21
						22
						23
○	○	○	○			24
○	○	○	○			25
○	○	○	○			26
○	○	○	○			27
						28
						29
						30
						31
						32
						33
						34
						35
						36
						37
						38
						39
						40
						41


**YG TAP
GENERAL**

TC411 SERIES

MF **ISO metric fine threads DIN 13**

- 🇩🇪 **Metrisches ISO-Feingewinde DIN 13**
- 🇫🇷 **ISO MÉTRIQUE PAS FINS DIN13**
- 🇮🇹 **ISO Metrico passo fine DIN 13**

Machine taps
Maschinengewindebohrer

► Suitable for tapping blind holes due to special flute geometry and excellent chip evacuation.

DIN 374



Hole type
2.5×D



Material groups

GS

HSS-E

DIN 374

6H

60°

C

R40

Bright

p.B309

Recommended ToolHolder

Plain Shank

TAPPING ER CHUCK

TAPPING CHUCK

ONE STEP TAPPING CHUCK

Unit : mm										
SIZE	Pitch	EDP No.	Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
ØD1	P	Bright	L1	L2	L3	ØD2	K	KI	Z	Ød1
M20 × 1.5		TC411726	17	125	50	16	12	15	4	18.5
M20 × 1.0		TC411736	14	125	50	16	12	15	4	19
M22 × 1.5		TC411766	17	125	50	18	14.5	17	4	20.5
M22 × 1.0		TC411776	14	125	50	18	14.5	17	4	21
M24 × 2.0		TC411796	20	140	54	18	14.5	17	4	22
M24 × 1.5		TC411806	20	140	54	18	14.5	17	4	22.5
M26 × 1.5		TC411856	20	140	54	18	14.5	17	4	24.5
M27 × 2.0		TC411876	20	140	54	20	16	19	4	25
M27 × 1.5		TC411886	20	140	54	20	16	19	4	25.5
M28 × 1.5		TC411916	20	140	54	20	16	19	4	26.5
M30 × 2.0		TC411966	22	150	57	22	18	21	4	28
M30 × 1.5		TC411976	22	150	57	22	18	21	4	28.5

◎: Excellent ○: Good

[illegible]

CARBIDE

HSS

YG TAP GENERAL

TD411 SERIES

MF

ISO metric fine threads DIN 13

Metrisches ISO-Feingewinde DIN 13

ISO MÉTRIQUE PAS FINS DIN13

ISO Metrico passo fine DIN 13

Machine taps
Maschinengewindebohrer

Suitable for tapping blind holes due to special flute geometry and excellent chip evacuation.

Geeignet zum Gewinden von Sacklöchern dank besonderer Nutengeometrie und ausgezeichneter Spanabfuhr.

DIN 374

Hole type

2.5×D

GS

HSS-E

DIN 374

6H

60°

C

R40

TiN

p.B309

Plain Shank

TAPPING ER CHUCK

TAPPING CHUCK

ONE STEP TAPPING CHUCK

Unit : mm

SIZE	Pitch	EDP No.	Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
ØD1	P	TiN	L1	L2	L3	ØD2	K	Kl	Z	Ød1
M4	× 0.5	TD411256	5	63	21	2.8	2.1	5	3	3.5
M5	× 0.5	TD411296	5	70	25	3.5	2.7	6	3	4.5
M6	× 0.75	TD411326	8	80	30	4.5	3.4	6	3	5.2
M6	× 0.5	TD411336	5	80	30	4.5	3.4	6	3	5.5
M7	× 0.75	TD411356	10	80	30	5.5	4.3	7	3	6.2
M8	× 1.0	TD411376	10	90	36	6	4.9	8	3	7
M8	× 0.75	TD411386	8	80	30	6	4.9	8	3	7.2
M8	× 0.5	TD411936	5	80	30	6	4.9	8	3	7.5
M10	× 1.25	TD411436	16	100	40	7	5.5	8	3	8.8
M10	× 1.0	TD411446	10	90	36	7	5.5	8	3	9
M10	× 0.75	TD411456	10	90	36	7	5.5	8	3	9.2
M12	× 1.5	TD411516	15	100	40	9	7	10	3	10.5
M12	× 1.25	TD411526	15	100	40	9	7	10	3	10.8
M12	× 1.0	TD411536	11	100	40	9	7	10	3	11
M14	× 1.5	TD411556	15	100	40	11	9	12	3	12.5
M14	× 1.25	TD411566	15	100	40	11	9	12	3	12.8
M14	× 1.0	TD411576	11	100	40	11	9	12	3	13
M16	× 1.5	TD411616	15	100	40	12	9	12	3	14.5

NEXT PAGE

ISO

	P										M					K				
Material Description	Non-alloy steel					Low alloy steel					High alloyed steel, and tool steel					Stainless steel				
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
HRc	13	25	28	32	30	10	29	32	38	15	35	15	23	10	10	26	3	25	21	
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommended	○	◎	◎	◎	◎	◎	◎	○		○	○	◎	◎				◎	◎		

ISO

	N										S					H				
Material Description	Aluminum-wrought alloy					Aluminum-cast, alloyed					Copper and Copper Alloys (Bronze / Brass)					Non Metallic Materials				
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
HRc	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400Rm	1050Rm	550	630	400
Recommended	○	○	○	◎	◎	○		◎												

B276

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

YG-1 CO., LTD.

CARBIDE

HSS

YG TAP GENERAL

TD411 SERIES

MF

ISO metric fine threads DIN 13

Metrisches ISO-Feingewinde DIN 13

ISO MÉTRIQUE PAS FINS DIN13

ISO Metrico passo fine DIN 13

Machine taps
Maschinengewindebohrer

Suitable for tapping blind holes due to special flute geometry and excellent chip evacuation.

Geeignet zum Gewinden von Sacklöchern dank besonderer Nutengeometrie und ausgezeichneter Spanabfuhr.

DIN 374

Hole type

2.5×D

GS

HSS-E

DIN 374

6H

60°

C

R40

TiN

p.B309

Plain Shank

TAPPING ER CHUCK

TAPPING CHUCK

ONE STEP TAPPING CHUCK

Unit : mm

SIZE	Pitch	EDP No.	Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
ØD1	P	TiN	L1	L2	L3	ØD2	K	Kl	Z	Ød1
M16	× 1.0	TD411626	12	100	40	12	9	12	3	15
M18	× 1.5	TD411676	17	110	44	14	11	14	4	16.5
M18	× 1.0	TD411686	13	110	44	14	11	14	4	17
M20	× 1.5	TD411726	17	125	50	16	12	15	4	18.5
M20	× 1.0	TD411736	14	125	50	16	12	15	4	19
M22	× 1.5	TD411766	17	125	50	18	14.5	17	4	20.5
M22	× 1.0	TD411776	14	125	50	18	14.5	17	4	21
M24	× 2.0	TD411796	20	140	54	18	14.5	17	4	22
M24	× 1.5	TD411806	20	140	54	18	14.5	17	4	22.5
M26	× 1.5	TD411856	20	140	54	18	14.5	17	4	24.5
M27	× 2.0	TD411876	20	140	54	20	16	19	4	25
M27	× 1.5	TD411886	20	140	54	20	16	19	4	25.5
M28	× 1.5	TD411916	20	140	54	20	16	19	4	26.5
M30	× 2.0	TD411966	22	150	57	22	18	21	4	28
M30	× 1.5	TD411976	22	150	57	22	18	21	4	28.5

NEXT PAGE

ISO

	P										M					K				
Material Description	Non-alloy steel					Low alloy steel					High alloyed steel, and tool steel					Stainless steel				
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
HRc	13	25	28	32	30	10	29	32	38	15	35	15	23	10	10	26	3	25	21	
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommended	○	◎	◎	◎	◎	◎	◎	○		○	○	◎	◎				◎	◎		

ISO

	N										S					H				
Material Description	Aluminum-wrought alloy					Aluminum-cast, alloyed					Copper and Copper Alloys (Bronze / Brass)					Non Metallic Materials				
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
HRc	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400Rm	1050Rm	550	630	400
Recommended	○	○	○	◎	◎	○		◎												

B277

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

YG-1 CO., LTD.

CARBIDE

HSS

YG TAP GENERAL

TC612 SERIES

M

ISO metric coarse threads DIN 13

Metrisches ISO-Gewinde DIN 13

ISO MÉTRIQUE DIN13

ISO Metrico passo grosso DIN 13

Machine taps
Maschinengewindebohrer

Suitable for tapping blind holes due to special flute geometry and excellent chip evacuation.

Geeignet zum Gewinden von Sacklöchern dank besonderer Nutengeometrie und ausgezeichneter Spanabfuhr.

DIN 352

Hole type

2.5×D

Material groups

GS

HSS-E

DIN 352

6H

60°

C

R20

Bright

p.B309

Recommended ToolHolder

Plain Shank
TAPPING ER CHUCK
TAPPING CHUCK
ONE STEP TAPPING CHUCK

Unit : mm

SIZE	Pitch	EDP No.	Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
ØD1	P	Bright	L1	L2	L3	ØD2	K	KI	Z	Ød1
M3	× 0.5	TC612206	11	40	18	3.5	2.7	6	3	2.5
M4	× 0.7	TC612246	13	45	21	4.5	3.4	6	3	3.3
M5	× 0.8	TC612286	16	52	26	6	4.9	8	3	4.2
M6	× 1.0	TC612316	18	56	27	6	4.9	8	3	5
M8	× 1.25	TC612366	20	63	34	6	4.9	8	3	6.8
M10	× 1.5	TC612426	22	70	38	7	5.5	8	3	8.5
M12	× 1.75	TC612506	24	80	45	9	7	10	3	10.2
M14	× 2.0	TC612546	26	80	45	11	9	12	3	12
M16	× 2.0	TC612606	27	80	45	12	9	12	3	14
M18	× 2.5	TC612656	30	95	58	14	11	14	4	15.5
M20	× 2.5	TC612706	32	95	58	16	12	15	4	17.5

ISO

	P										M					K				
Material Description	Non-alloy steel					Low alloy steel					High alloyed steel, and tool steel					Stainless steel				
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
HRc	13	25	28	32	30	10	29	32	38	15	35	15	23	10	10	26	3	25	21	21
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommended	○	◎	◎	◎	◎	◎	◎	○		○	○						◎	◎		

	N										S					H				
Material Description	Aluminum-wrought alloy					Aluminum-cast, alloyed					Copper and Copper Alloys (Bronze / Brass)					Non Metallic Materials				
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
HRc	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400Rm	1050Rm	550	630	400
Recommended	○		○	○	◎	○		◎												

B282

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

YG-1 CO., LTD.

CARBIDE

HSS

YG TAP GENERAL

TC127 SERIES

M

ISO metric coarse threads DIN 13

Metrisches ISO-Gewinde DIN 13

ISO MÉTRIQUE DIN13

ISO Metrico passo grosso DIN 13

Machine taps
Maschinengewindebohrer

Suitable for through hole in more cutting speed than other taps due to thick web.

Geeignet für Durchgangslöcher in höherer Schnittgeschwindigkeit als bei anderen Gewindebohrern dank größerer Kerndicke.

DIN 371

Hole type

3.0×D

Material groups

GS

HSS-E

DIN 371

6H

60°

B

Bright

p.B309

Recommended ToolHolder

Plain Shank
TAPPING ER CHUCK
TAPPING CHUCK
ONE STEP TAPPING CHUCK

Unit : mm

SIZE	Pitch	EDP No.	Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
ØD1	P	Bright	L1	L2	L3	ØD2	K	KI	Z	Ød1
M2	× 0.4	TC127136	8	45	13	2.8	2.1	5	3	1.6
M2.2	× 0.45	TC127156	8	45	13	2.8	2.1	5	3	1.75
*M2.3	× 0.4	TC127196	8	45	13	2.8	2.1	5	3	1.9
M2.5	× 0.45	TC127176	9	50	15	2.8	2.1	5	3	2.05
*M2.6	× 0.45	TC127496	9	50	15	2.8	2.1	5	3	2.1
M3	× 0.5	TC127206	11	56	18	3.5	2.7	6	3	2.5
M3.5	× 0.6	TC127226	12	56	20	4	3	6	3	2.9
M4	× 0.7	TC127246	13	63	21	4.5	3.4	6	3	3.3
M4.5	× 0.75	TC127266	14	70	25	6	4.9	8	3	3.7
M5	× 0.8	TC127286	15	70	25	6	4.9	8	3	4.2
M6	× 1.0	TC127316	17	80	30	6	4.9	8	3	5
M7	× 1.0	TC127346	17	80	30	7	5.5	8	3	6
M8	× 1.25	TC127366	20	90	35	8	6.2	9	3	6.8
M9	× 1.25	TC127396	20	90	35	9	7	10	3	7.8
M10	× 1.5	TC127426	22	100	39	10	8	11	3	8.5
M11	× 1.5	TC127466	22	100	39	11	9	12	3	9.5
M12	× 1.75	TC127506	24	110	44	12	9	12	3	10.2

ISO

	P										M					K				
Material Description	Non-alloy steel					Low alloy steel					High alloyed steel, and tool steel					Stainless steel				
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
HRc	13	25	28	32	30	10	29	32	38	15	35	15	23	10	10	26	3	25	21	21
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommended	○	◎	◎	◎	◎	◎	◎	○		○	○						◎	◎		

	N										S					H				
Material Description	Aluminum-wrought alloy					Aluminum-cast, alloyed					Copper and Copper Alloys (Bronze / Brass)					Non Metallic Materials				
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
HRc	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400Rm	1050Rm	550	630	400
Recommended	○		○	○	◎	○		◎												

B283

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

YG-1 CO., LTD.

CARBIDE

HSS

YG TAP GENERAL

TD127 SERIES

M

ISO metric coarse threads DIN 13

Metrisches ISO-Gewinde DIN 13

ISO MÉTRIQUE DIN13

ISO Metrico passo grosso DIN 13

Machine taps
Maschinengewindebohrer

Suitable for through hole in more cutting speed than other taps due to thick web.

Geeignet für Durchgangslöcher in höherer Schnittgeschwindigkeit als bei anderen Gewindebohrern dank größerer Kerndicke.

DIN 371

Hole type
3.0×D

Material groups

GS

HSS-E

DIN 371

6H

60°

B

TiN

p.B309

Plain Shank

TAPPING ER CHUCK

TAPPING CHUCK

ONE STEP TAPPING CHUCK

Unit : mm

SIZE	Pitch	EDP No.	Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
ØD1	P	TiN	L1	L2	L3	ØD2	K	KI	Z	Ød1
M2	× 0.4	TD127136	8	45	13	2.8	2.1	5	3	1.6
M2.2	× 0.45	TD127156	8	45	13	2.8	2.1	5	3	1.75
*M2.3	× 0.4	TD127196	8	45	13	2.8	2.1	5	3	1.9
M2.5	× 0.45	TD127176	9	50	15	2.8	2.1	5	3	2.05
*M2.6	× 0.45	TD127496	9	50	15	2.8	2.1	5	3	2.1
M3	× 0.5	TD127206	11	56	18	3.5	2.7	6	3	2.5
M3.5	× 0.6	TD127226	12	56	20	4	3	6	3	2.9
M4	× 0.7	TD127246	13	63	21	4.5	3.4	6	3	3.3
M4.5	× 0.75	TD127266	14	70	25	6	4.9	8	3	3.7
M5	× 0.8	TD127286	15	70	25	6	4.9	8	3	4.2
M6	× 1.0	TD127316	17	80	30	6	4.9	8	3	5
M7	× 1.0	TD127346	17	80	30	7	5.5	8	3	6
M8	× 1.25	TD127366	20	90	35	8	6.2	9	3	6.8
M9	× 1.25	TD127396	20	90	35	9	7	10	3	7.8
M10	× 1.5	TD127426	22	100	39	10	8	11	3	8.5
M11	× 1.5	TD127466	22	100	39	11	9	12	3	9.5
M12	× 1.75	TD127506	24	110	44	12	9	12	3	10.2

► *DIN profile not ISO

ISO

P

Non-alloy steel

Low alloy steel

High alloyed steel, and tool steel

M

Stainless steel

Grey cast iron

Nodular cast iron

Malleable cast iron

K

ISO

N

Aluminum-wrought alloy

Aluminum-cast, alloyed

Copper and Copper Alloys (Bronze / Brass)

Non Metallic Materials

S

Heat Resistant Super Alloys

Titanium Alloys

Hardened steel

Chilled Cast Iron

Hardened Cast Iron

H

VDI 3323

HRc

HB

Recommended

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

125

13

25

28

32

10

29

32

38

15

35

15

23

10

10

26

3

25

130

21

○

◎

◎

◎

◎

◎

◎

○

○

◎

◎

○

○

○

○

◎

◎

◎

○

○

ISO

N

Aluminum-wrought alloy

Aluminum-cast, alloyed

Copper and Copper Alloys (Bronze / Brass)

Non Metallic Materials

S

Heat Resistant Super Alloys

Titanium Alloys

Hardened steel

Chilled Cast Iron

Hardened Cast Iron

H

VDI 3323

HRc

HB

Recommended

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

60

100

75

90

130

110

90

100

200

280

250

350

320

400Rm

1050Rm

550

630

400

550

○

○

○

◎

○

◎

B284

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

YG-1 CO., LTD.

CARBIDE

HSS

YG TAP GENERAL

TC122 SERIES

M

ISO metric coarse threads DIN 13

Metrisches ISO-Gewinde DIN 13

ISO MÉTRIQUE DIN13

ISO Metrico passo grosso DIN 13

Machine taps
Maschinengewindebohrer

Suitable for through hole in more cutting speed than other taps due to thick web.

Geeignet für Durchgangslöcher in höherer Schnittgeschwindigkeit als bei anderen Gewindebohrern dank größerer Kerndicke.

DIN 352

Hole type
3.0×D

Material groups

GS

HSS-E

DIN 352

6H

60°

B

Bright

p.B309

Plain Shank

TAPPING ER CHUCK

TAPPING CHUCK

ONE STEP TAPPING CHUCK

Unit : mm

SIZE	Pitch	EDP No.	Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
ØD1	P	Bright	L1	L2	L3	ØD2	K	KI	Z	Ød1
M2	× 0.4	TC122136	8	36	13	2.8	2.1	5	3	1.6
M2.5	× 0.45	TC122176	9	40	15	2.8	2.1	5	3	2.05
M3	× 0.5	TC122206	11	40	18	3.5	2.7	6	3	2.5
M4	× 0.7	TC122246	13	45	21	4.5	3.4	6	3	3.3
M5	× 0.8	TC122286	16	52	26	6	4.9	8	3	4.2
M6	× 1.0	TC122316	18	56	27	6	4.9	8	3	5
M8	× 1.25	TC122366	20	63	34	6	4.9	8	3	6.8
M10	× 1.5	TC122426	22	70	38	7	5.5	8	3	8.5
M12	× 1.75	TC122506	24	80	45	9	7	10	3	10.2
M14	× 2.0	TC122546	26	80	45	11	9	12	3	12
M16	× 2.0	TC122606	27	80	45	12	9	12	3	14

► *DIN profile not ISO

ISO

P

Non-alloy steel

Low alloy steel

High alloyed steel, and tool steel

M

Stainless steel

Grey cast iron

Nodular cast iron

Malleable cast iron

K

ISO

N

Aluminum-wrought alloy

Aluminum-cast, alloyed

Copper and Copper Alloys (Bronze / Brass)

Non Metallic Materials

S

Heat Resistant Super Alloys

Titanium Alloys

Hardened steel

Chilled Cast Iron

Hardened Cast Iron

H

VDI 3323

HRc

HB

Recommended

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

125

13

25

28

32

10

29

32

38

15

35

15

23

10

10

26

3

25

130

21

○

◎

◎

◎

◎

◎

◎

○

○

◎

◎

○

○

○

○

◎

◎

◎

○

○

ISO

N

Aluminum-wrought alloy

Aluminum-cast, alloyed

Copper and Copper Alloys (Bronze / Brass)

Non Metallic Materials

S

Heat Resistant Super Alloys

Titanium Alloys

Hardened steel

Chilled Cast Iron

Hardened Cast Iron

H

VDI 3323

HRc

HB

Recommended

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

60

100

75

90

130

110

90

100

200

280

250

350

320

400Rm

1050Rm

550

630

400

550

○

○

○

◎

○

◎

B285

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

YG-1 CO., LTD.

CARBIDE

HSS

YG TAP GENERAL

TC222 SERIES

MF

ISO metric fine threads DIN 13

Metrisches ISO-Feingewinde DIN 13

ISO MÉTRIQUE PAS FINS DIN13

ISO Metrico passo fine DIN 13

Machine taps
Maschinengewindebohrer


Suitable for through hole in more cutting speed than other taps due to thick web.


Geeignet für Durchgangslöcher in höherer Schnittgeschwindigkeit als bei anderen Gewindebohrern dank größerer Kerndicke.


DIN 374





Hole type
3.0×D











Material groups

GS

HSS-E

DIN 374

6H

60°

B

Bright



p.B309

Recommended ToolHolder

Plain Shank
TAPPING ER CHUCK
TAPPING CHUCK
ONE STEP TAPPING CHUCK

Unit : mm

SIZE	Pitch	EDP No.	Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
ØD1	P	Bright	L1	L2	L3	ØD2	K	KI	Z	Ød1
M4	× 0.5	TC222256	10	63	21	2.8	2.1	5	3	3.5
M5	× 0.5	TC222296	11	70	25	3.5	2.7	6	3	4.5
M6	× 0.75	TC222326	13	80	30	4.5	3.4	6	3	5.2
M6	× 0.5	TC222336	13	80	30	4.5	3.4	6	3	5.5
M7	× 0.75	TC222356	14	80	30	5.5	4.3	7	3	6.2
M8	× 1.0	TC222376	17	90	36	6	4.9	8	3	7
M8	× 0.75	TC222386	14	80	30	6	4.9	8	3	7.2
M8	× 0.5	TC222936	14	80	30	6	4.9	8	3	7.5
M10	× 1.25	TC222436	22	100	40	7	5.5	8	3	8.8
M10	× 1.0	TC222446	18	90	36	7	5.5	8	3	9
M10	× 0.75	TC222456	18	90	36	7	5.5	8	3	9.2
M12	× 1.5	TC222516	22	100	40	9	7	10	3	10.5
M12	× 1.25	TC222526	22	100	40	9	7	10	3	10.8
M12	× 1.0	TC222536	18	100	40	9	7	10	3	11
M14	× 1.5	TC222556	22	100	40	11	9	12	3	12.5
M14	× 1.25	TC222566	22	100	40	11	9	12	3	12.8
M14	× 1.0	TC222576	18	100	40	11	9	12	3	13

► NEXT PAGE

ISO

Material Description

VDI 3323

HRC

HB

Recommended

P										M				K					
Non-alloy steel					Low alloy steel					High alloyed steel, and tool steel	Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron	
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
125	13	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25	21	21
125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
○	◎	◎	◎	◎	◎	◎	◎	○	○	○	◎	◎	○	◎	◎	◎	◎	○	○

◎ : Excellent ○ : Good

ISO

Material Description

VDI 3323

HRC

HB

Recommended

N										S						H				
Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys				Titanium Alloys		Hardened steel	Chilled Cast Iron	Hardened Cast Iron		
21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
15	30	25	38	34	15	30	25	38	34	200	280	250	350	320	400Rm	1050Rm	550	630	400	550
60	100	75	90	130	110	90	100													
○	○	○	◎	◎	○		◎													

B286

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

YG-1 CO., LTD.

CARBIDE

HSS

YG TAP GENERAL

TC222 SERIES

MF

ISO metric fine threads DIN 13

Metrisches ISO-Feingewinde DIN 13

ISO MÉTRIQUE PAS FINS DIN13

ISO Metrico passo fine DIN 13

Machine taps
Maschinengewindebohrer


Suitable for through hole in more cutting speed than other taps due to thick web.


Geeignet für Durchgangslöcher in höherer Schnittgeschwindigkeit als bei anderen Gewindebohrern dank größerer Kerndicke.


DIN 374





Hole type
3.0×D











Material groups

GS

HSS-E

DIN 374

6H

60°

B

Bright



p.B309

Recommended ToolHolder

Plain Shank
TAPPING ER CHUCK
TAPPING CHUCK
ONE STEP TAPPING CHUCK

Unit : mm

SIZE	Pitch	EDP No.	Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
ØD1	P	Bright	L1	L2	L3	ØD2	K	KI	Z	Ød1
M16	× 1.5	TC222616	22	100	40	12	9	12	3	14.5
M16	× 1.0	TC222626	18	100	40	12	9	12	3	15
M18	× 1.5	TC222676	25	110	44	14	11	14	4	16.5
M18	× 1.0	TC222686	20	110	44	14	11	14	4	17
M20	× 1.5	TC222726	25	125	50	16	12	15	4	18.5
M20	× 1.0	TC222736	20	125	50	16	12	15	4	19
M22	× 1.5	TC222766	25	125	50	18	14.5	17	4	20.5
M22	× 1.0	TC222776	20	125	50	18	14.5	17	4	21
M24	× 2.0	TC222796	27	140	54	18	14.5	17	4	22
M24	× 1.5	TC222806	27	140	54	18	14.5	17	4	22.5
M26	× 1.5	TC222856	28	140	54	18	14.5	17	4	24.5
M27	× 2.0	TC222876	28	140	54	20	16	19	4	25
M27	× 1.5	TC222886	28	140	54	20	16	19	4	25.5
M28	× 1.5	TC222916	28	140	54	20	16	19	4	26.5
M30	× 2.0	TC222966	30	150	57	22	18	21	4	28
M30	× 1.5	TC222976	30	150	57	22	18	21	4	28.5

◎ : Excellent ○ : Good

ISO

Material Description

VDI 3323

HRC

HB

Recommended

P										M				K					
Non-alloy steel					Low alloy steel					High alloyed steel, and tool steel	Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron	
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
125	13	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25	21	21
125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
○	◎	◎	◎	◎	◎	◎	◎	○	○	○	◎	◎	○	◎	◎	◎	◎	○	○

◎ : Excellent ○ : Good

ISO

Material Description

VDI 3323

HRC

HB

Recommended

N										S						H				
Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys				Titanium Alloys		Hardened steel	Chilled Cast Iron	Hardened Cast Iron		
21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
15	30	25	38	34	15	30	25	38	34	200	280	250	350	320	400Rm	1050Rm	550	630	400	550
60	100	75	90	130	110	90	100													
○	○	○	◎	◎	○		◎													

B287

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

YG-1 CO., LTD.

UNC Unified coarse threads

Unified Grobgewinde
UNC
Unificato passo grosso



Machine taps
Maschinengewindebohrer

► Suitable for through hole in more cutting speed than other taps due to thick web.

► Geeignet für Durchgangslöcher in höherer Schnittgeschwindigkeit als bei anderen Gewindebohrern dank größerer Kerndicke.



Hole type
3.0×D



Material groups: **GS** HSS-E DIN 371/376 2B 60° B Bright p.B309

Recommended ToolHolder: Plain Shank TAPPING ER CHUCK ONE STEP TAPPING CHUCK

SIZE	TPI	EDP No.	Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
ØD1		Bright	L1	L2	L3	ØD2	K	KI	Z	Ød1
#4	- 40UNC	TC214162	11	56	18	3.5	2.7	6	3	2.3
#5	- 40UNC	TC214202	11	56	18	3.5	2.7	6	3	2.6
#6	- 32UNC	TC214242	12	56	20	4	3	6	3	2.85
#8	- 32UNC	TC214282	13	63	21	4.5	3.4	6	3	3.5
#10	- 24UNC	TC214322	15	70	25	6	4.9	8	3	3.9
#12	- 24UNC	TC214362	16	80	30	6	4.9	8	3	4.5
1/4	- 20UNC	TC214402	17	80	30	7	5.5	8	3	5.2
5/16	- 18UNC	TC214442	20	90	35	8	6.2	9	3	6.6
3/8	- 16UNC	TC214482	22	100	39	9	7	10	3	8
7/16	- 14UNC	TC214522	22	100	40	8	6.2	9	3	9.4
1/2	- 13UNC	TC214562	25	110	44	9	7	10	3	10.75
9/16	- 12UNC	TC214602	26	110	44	11	9	12	3	12.25
5/8	- 11UNC	TC214642	27	110	44	12	9	12	3	13.5
3/4	- 10UNC	TC214702	30	125	50	14	11	14	4	16.5
7/8	- 9UNC	TC214742	32	140	54	18	14.5	17	4	19.5
1	- 8UNC	TC214782	36	160	60	20	16	19	4	22.25
1-1/8	- 7UNC	TC214822	40	180	70	22	18	21	4	25

► DIN 371(#4~3/8) and DIN 376(7/16~1-1/8)

ISO	P										M					K				
Material Description	Non-alloy steel					Low alloy steel					High alloy steel, and tool steel					Stainless steel				
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
HRc	13	25	28	32	30	10	29	32	38	15	35	15	23	10	10	26	3	25	21	21
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommended	○	◎	◎	◎	◎	◎	◎	○	○	○	○	○	○	○	○	○	◎	◎	○	○
ISO	N										S					H				
Material Description	Aluminum-wrought alloy					Aluminum-cast, alloyed					Copper and Copper Alloys (Bronze / Brass)					Non Metallic Materials				
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
HRc	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400Rm	1050Rm	550	630	400
Recommended	○	○	○	◎	◎	○	○	◎												

UNF Unified fine threads

Unified Feingewinde
UNF
Unificato passo fine



Machine taps
Maschinengewindebohrer

► Suitable for through hole in more cutting speed than other taps due to thick web.

► Geeignet für Durchgangslöcher in höherer Schnittgeschwindigkeit als bei anderen Gewindebohrern dank größerer Kerndicke.



Hole type
3.0×D



Material groups: **GS** HSS-E DIN 371/374 2B 60° B Bright p.B309

Recommended ToolHolder: Plain Shank TAPPING ER CHUCK ONE STEP TAPPING CHUCK

SIZE	TPI	EDP No.	Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
ØD1		Bright	L1	L2	L3	ØD2	K	KI	Z	Ød1
#4	- 48UNF	TC234182	11	56	18	3.5	2.7	6	3	2.4
#5	- 44UNF	TC234222	11	56	18	3.5	2.7	6	3	2.7
#6	- 40UNF	TC234262	12	56	20	4	3	6	3	3
#8	- 36UNF	TC234302	13	63	21	4.5	3.4	6	3	3.5
#10	- 32UNF	TC234342	15	70	25	6	4.9	8	3	4.1
#12	- 28UNF	TC234382	16	80	30	6	4.9	8	3	4.7
1/4	- 28UNF	TC234422	17	80	30	7	5.5	8	3	5.5
5/16	- 24UNF	TC234462	17	90	35	8	6.2	9	3	6.9
3/8	- 24UNF	TC234502	18	100	39	9	7	10	3	8.5
7/16	- 20UNF	TC234542	22	100	40	8	6.2	9	3	9.9
1/2	- 20UNF	TC234582	22	100	40	9	7	10	3	11.5
9/16	- 18UNF	TC234622	22	100	40	11	9	12	3	12.9
5/8	- 18UNF	TC234662	22	100	40	12	9	12	3	14.5
3/4	- 16UNF	TC234722	25	110	44	14	11	14	4	17.5
7/8	- 14UNF	TC234762	26	125	50	18	14.5	17	4	20.5
1	- 12UNF	TC234802	28	140	54	18	14.5	17	4	23.25
1-1/8	- 12UNF	TC234842	30	150	60	22	18	21	4	26.5

► DIN 371(#4~3/8) and DIN 374(7/16~1-1/8)

ISO	P										M					K				
Material Description	Non-alloy steel					Low alloy steel					High alloy steel, and tool steel					Stainless steel				
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
HRc	13	25	28	32	30	10	29	32	38	15	35	15	23	10	10	26	3	25	21	21
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommended	○	◎	◎	◎	◎	○	◎	◎	○	○	○	○	○	○	○	○	◎	◎	○	○
ISO	N										S					H				
Material Description	Aluminum-wrought alloy					Aluminum-cast, alloyed					Copper and Copper Alloys (Bronze / Brass)					Non Metallic Materials				
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
HRc	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400Rm	1050Rm	550	630	400
Recommended	○	○	○	◎	◎	○	○	◎												

CARBIDE

HSS

YG TAP GENERAL

TD227

SERIES

M

ISO metric coarse threads DIN 13

Metrisches ISO-Gewinde DIN 13

ISO MÉTRIQUE DIN13

ISO Metrico passo grosso DIN 13

Machine taps
Maschinengewindebohrer

Suitable for through hole in more cutting speed than other taps due to thick web.

Geeignet für Durchgangslöcher in höherer Schnittgeschwindigkeit als bei anderen Gewindebohrern dank größerer Kerndicke.

DIN 376

Hole type

3.0×D

GS

HSS-E

DIN 376

6H

60°

B

TiN

p.B309

Plain Shank

TAPPING ER CHUCK

TAPPING CHUCK

ONE STEP TAPPING CHUCK

Unit : mm

SIZE	Pitch	EDP No.	Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
ØD1	P	TiN	L1	L2	L3	ØD2	K	KI	Z	Ød1
M3	× 0.5	TD227206	11	56	18	2.2	1.8	5	3	2.5
M3.5	× 0.6	TD227226	12	56	20	2.5	2.1	5	3	2.9
M4	× 0.7	TD227246	13	63	21	2.8	2.1	5	3	3.3
M4.5	× 0.75	TD227266	14	70	25	3.5	2.7	6	3	3.7
M5	× 0.8	TD227286	15	70	25	3.5	2.7	6	3	4.2
M6	× 1.0	TD227316	17	80	30	4.5	3.4	6	3	5
M7	× 1.0	TD227346	17	80	30	5.5	4.3	7	3	6
M8	× 1.25	TD227366	20	90	36	6	4.9	8	3	6.8
M9	× 1.25	TD227396	20	90	36	7	5.5	8	3	7.8
M10	× 1.5	TD227426	22	100	40	7	5.5	8	3	8.5
M11	× 1.5	TD227466	22	100	40	8	6.2	9	3	9.5
M12	× 1.75	TD227506	24	110	44	9	7	10	3	10.2
M14	× 2.0	TD227546	26	110	44	11	9	12	3	12
M16	× 2.0	TD227606	27	110	44	12	9	12	3	14
M18	× 2.5	TD227656	30	125	50	14	11	14	4	15.5
M20	× 2.5	TD227706	32	140	54	16	12	15	4	17.5
M22	× 2.5	TD227746	32	140	54	18	14.5	17	4	19.5
M24	× 3.0	TD227786	34	160	60	18	14.5	17	4	21
M27	× 3.0	TD227866	36	160	60	20	16	19	4	24
M30	× 3.5	TD227946	40	180	70	22	18	21	4	26.5

ISO

	P										M					K				
Material Description	Non-alloy steel					Low alloy steel					High alloy steel, and tool steel					Stainless steel				
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
HRC	13	25	28	32	30	10	29	32	38	15	35	15	23	10	10	26	3	25	21	21
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommended	○	◎	◎	◎	◎	◎	◎	○		○	○						◎	◎		
ISO	N										S					H				
Material Description	Aluminum-wrought alloy					Aluminum-cast, alloyed					Copper and Copper Alloys (Bronze / Brass)					Non Metallic Materials				
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
HRC	21	22	23	24	25	26	27	28	29	30	15	30	25	38	34	55	60	42	55	55
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400Rm	1050Rm	550	630	400
Recommended	○		○	○	◎	○		◎												

◎ : Excellent ○ : Good

B294

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

YG-1 CO., LTD.

CARBIDE

HSS

YG TAP GENERAL

TC211

SERIES

M

ISO metric coarse threads DIN 13

Metrisches ISO-Gewinde DIN 13

ISO MÉTRIQUE DIN13

ISO Metrico passo grosso DIN 13

Machine taps
Maschinengewindebohrer

Left spiral flute and right hand thread tap to push chips ahead in powerful than spiral point taps.

Rechtsschneidender Gewindebohrer mit Linksdrall um kraftvoller nach vorne zu entspanen als mit Gewindebohrern mit Rechtsdrall.

DIN 371

Hole type

3.0×D

GS

HSS-E

DIN 371/376

6H

60°

C

Bright

L20

p.B309

Plain Shank

TAPPING ER CHUCK

TAPPING CHUCK

ONE STEP TAPPING CHUCK

Unit : mm

SIZE	Pitch	EDP No.	Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
ØD1	P	Bright	L1	L2	L3	ØD2	K	KI	Z	Ød1
M2	× 0.4	TC211136	8	45	13	2.8	2.1	5	3	1.6
M2.2	× 0.45	TC211156	8	45	13	2.8	2.1	5	3	1.75
*M2.3	× 0.4	TC211196	8	45	13	2.8	2.1	5	3	1.9
M2.5	× 0.45	TC211176	9	50	15	2.8	2.1	5	3	2.05
*M2.6	× 0.45	TC211496	9	50	15	2.8	2.1	5	3	2.1
M3	× 0.5	TC211206	11	56	18	3.5	2.7	6	3	2.5
M3.5	× 0.6	TC211226	12	56	20	4	3	6	3	2.9
M4	× 0.7	TC211246	13	63	21	4.5	3.4	6	3	3.3
M4.5	× 0.75	TC211266	14	70	25	6	4.9	8	3	3.7
M5	× 0.8	TC211286	15	70	25	6	4.9	8	3	4.2
M6	× 1.0	TC211316	17	80	30	6	4.9	8	3	5
M7	× 1.0	TC211346	17	80	30	7	5.5	8	3	6
M8	× 1.25	TC211366	20	90	35	8	6.2	9	3	6.8
M9	× 1.25	TC211396	20	90	35	9	7	10	3	7.8
M10	× 1.5	TC211426	22	100	39	10	8	11	3	8.5
M11	× 1.5	TC211466	22	100	40	8	6.2	9	3	9.5
M12	× 1.75	TC211506	24	110	44	9	7	10	3	10.2
M14	× 2.0	TC211546	26	110	44	11	9	12	3	12
M16	× 2.0	TC211606	27	110	44	12	9	12	3	14
M18	× 2.5	TC211656	30	125	50	14	11	14	4	15.5
M20	× 2.5	TC211706	32	140	54	16	12	15	4	17.5
M22	× 2.5	TC211746	32	140	54	18	14.5	17	4	19.5
M24	× 3.0	TC211786	34	160	60	18	14.5	17	4	21
M27	× 3.0	TC211866	36	160	60	20	16	19	4	24
M30	× 3.5	TC211946	40	180	70	22	18	21	4	26.5

◎ : Excellent ○ : Good

B295

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

YG-1 CO., LTD.

CARBIDE

HSS

YG TAP GENERAL

T7109 SERIES

M

ISO metric coarse threads DIN 13

Metrisches ISO-Gewinde DIN 13

ISO MÉTRIQUE DIN13

ISO Metrico passo grosso DIN 13

Sets of taps
Gewindebohrer-Satz

This tap is a serial hand tap in set, First, Second and Bottoming.

Bottoming tap of set has final internal thread dimensions only.

Dies ist ein Handgewindebohrer im Satz mit Vor-, Mittel- und Fertigschneider.

Nur der Fertigschneider kann das gewünschte Gewinde schneiden.

First

Second

Bottoming

Hole type

2.0×D

60°

P

ØD1

ØD2

L1

L2

L3

KI

Ød1

GS

HSS

DIN 352

6H

60°

I/II/III

Bright

p.B309

Plain Shank

TAPPING ER CHUCK

TAPPING CHUCK

ONE STEP TAPPING CHUCK

Unit : mm

SIZE	Pitch	EDP No.	Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
ØD1	P	Bright	L1	L2	L3	ØD2	K	KI	Z	Ød1
M22 × 2.5		T7109749	32	100	62	18	14.5	17	4	19.5
M24 × 3.0		T7109789	34	110	69	18	14.5	17	4	21
M27 × 3.0		T7109869	36	110	69	20	16	19	4	24
M30 × 3.5		T7109949	40	125	77	22	18	21	4	26.5
M33 × 3.5		T7109A49	40	125	77	25	20	23	4	29.5
M36 × 4.0		T7109B39	50	150	88	28	22	25	4	32
M39 × 4.0		T7109C09	50	150	88	32	24	27	4	35
M42 × 4.5		T7109C89	56	150	88	32	24	27	4	37.5
M45 × 4.5		T7109D59	58	160	93	36	29	32	4	40.5
M48 × 5.0		T7109E29	65	180	102	36	29	32	4	43
M52 × 5.0		T7109F39	65	180	102	40	32	35	4	47

► *DIN profile not ISO

ISO

	P										M					K				
	Non-alloy steel					Low alloy steel					High alloy steel, and tool steel					Stainless steel				
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
HRc	125	13	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25	21	
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommended	○	○	○	○		○	○										○	○		

ISO

	N										S					H				
	Aluminum-wrought alloy					Aluminum-cast, alloyed					Copper and Copper Alloys (Bronze / Brass)					Non Metallic Materials				
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
HRc	60	100	75	90	130	110	90	100			200	280	250	350	320	400Rm	1050Rm	550	630	400
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400Rm	1050Rm	550	630	400
Recommended					○	○	○													

YG-1 CO., LTD.

B300

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

CARBIDE

HSS

YG TAP GENERAL

T7309 SERIES

MF

ISO metric fine threads DIN 13

Metrisches ISO-Gewinde DIN 13

ISO MÉTRIQUE PAS FINS DIN13

ISO Metrico passo fine DIN 13

Sets of taps
Gewindebohrer-Satz

This tap is a serial hand tap in set, First and Bottoming.

Bottoming tap of set has final internal thread dimensions only.

Handgewindebohrersatz mit Vor- und Fertigschneider.

Nur der Fertigschneider kann das gewünschte Gewinde schneiden.

First

Bottoming

Hole type

2.0×D

60°

P

ØD1

ØD2

L1

L2

L3

KI

Ød1

GS

HSS

DIN 2181

6H

60°

I/III

Bright

p.B309

Plain Shank

TAPPING ER CHUCK

TAPPING CHUCK

ONE STEP TAPPING CHUCK

Unit : mm

SIZE	Pitch	EDP No.	Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
ØD1	P	Bright	L1	L2	L3	ØD2	K	KI	Z	Ød1
M3 × 0.35		T7309219	9	40	18	3.5	2.7	6	3	2.65
M4 × 0.5		T7309259	10	45	18	4.5	3.4	6	3	3.5
M5 × 0.5		T7309299	13	52	22	6	4.9	8	3	4.5
M6 × 0.75		T7309329	14	56	24	6	4.9	8	3	5.2
M6 × 0.5		T7309339	13	56	24	6	4.9	8	3	5.5
M7 × 0.75		T7309359	14	56	27	6	4.9	8	3	6.2
M8 × 1.0		T7309379	17	63	27	6	4.9	8	3	7
M8 × 0.75		T7309389	14	63	27	6	4.9	8	3	7.2
M8 × 0.5		T7309939	14	63	27	6	4.9	8	3	7.5
M9 × 1.0		T7309409	17	63	27	7	5.5	8	4	8
M10 × 1.25		T7309439	22	70	32	7	5.5	8	4	8.8
M10 × 1.0		T7309449	18	63	27	7	5.5	8	4	9
M10 × 0.75		T7309459	18	63	27	7	5.5	8	4	9.2
M11 × 1.0		T7309479	18	63	27	8	6.2	9	4	10
M12 × 1.5		T7309519	20	70	32	9	7	10	4	10.5
M12 × 1.25		T7309529	20	70	32	9	7	10	4	10.8
M12 × 1.0		T7309539	18	70	32	9	7	10	4	11
M13 × 1.5		T7309N19	20	70	32	11	9	12	4	11.5
M13 × 1.0		T7309N29	18	70	32	11	9	12	4	12
M14 × 1.5		T7309559	20	70	32	11	9	12	4	12.5
M14 × 1.25		T7309569	20	70	32	11	9	12	4	12.8
M14 × 1.0		T7309579	18	70	32	11	9	12	4	13
M15 × 1.5		T7309589	20	70	32	12	9	12	4	13.5
M15 × 1.0		T7309599	18	70	32	12	9	12	4	14
M16 × 1.5		T7309619	20	70	32	12	9	12	4	14.5

► NEXT PAGE

ISO

	P										M					K				
	Non-alloy steel					Low alloy steel					High alloy steel, and tool steel					Stainless steel				
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
HRc	125	13	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25	21	
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommended	○	○	○	○		○	○										○	○		

ISO

	N										S					H				
	Aluminum-wrought alloy					Aluminum-cast, alloyed					Copper and Copper Alloys (Bronze / Brass)					Non Metallic Materials				
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
HRc	60	100	75	90	130	110	90	100			200	280	250	350	320	400Rm	1050Rm	550	630	400
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400Rm	1050Rm	550	630	400
Recommended					○	○	○													

YG-1 CO., LTD.

B301

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

CARBIDE

HSS

YG TAP GENERAL

T7309 SERIES

MF

ISO metric fine threads DIN 13

Metrisches ISO-Feingewinde DIN 13

ISO MÉTRIQUE PAS FINS DIN13

ISO Metrico passo fine DIN 13

Sets of taps
Gewindebohrer-Satz

This tap is a serial hand tap in set, First and Bottoming.

Bottoming tap of set has final internal thread dimensions only.

Handgewindebohrersatz mit Vor- und Fertigschneider.

Nur der Fertigschneider kann das gewünschte Gewinde schneiden.

First

Bottoming

Hole type

2.0×D

60°

P

Ø d1

ØD2

ØD1

L1

L2

L3

KI

60°

P

Ø d1

Material groups

GS

HSS

DIN 2181

6H

60°

I/III

Bright

p.B309

Recommended ToolHolder

Plain Shank
TAPPING ER CHUCK
TAPPING CHUCK
ONE STEP TAPPING CHUCK

Unit : mm

SIZE	Pitch	EDP No.	Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
ØD1	P	Bright	L1	L2	L3	ØD2	K	KI	Z	Ød1
M16 × 1.0		T7309629	18	70	32	12	9	12	4	15
M18 × 2.0		T7309669	22	80	35	14	11	14	4	16
M18 × 1.5		T7309679	22	80	35	14	11	14	4	16.5
M18 × 1.0		T7309689	18	80	35	14	11	14	4	17
M20 × 2.0		T7309719	22	80	35	16	12	15	4	18
M20 × 1.5		T7309729	22	80	35	16	12	15	4	18.5
M20 × 1.0		T7309739	18	80	35	16	12	15	4	19
M22 × 2.0		T7309759	22	80	35	18	14.5	17	4	20
M22 × 1.5		T7309769	22	80	35	18	14.5	17	4	20.5
M22 × 1.0		T7309779	18	80	35	18	14.5	17	4	21
M24 × 2.0		T7309799	22	90	40	18	14.5	17	4	22
M24 × 1.5		T7309809	22	90	40	18	14.5	17	4	22.5
M24 × 1.0		T7309819	18	90	40	18	14.5	17	4	23
M25 × 1.5		T7309839	22	90	40	18	14.5	17	4	23.5
M25 × 1.0		T7309849	18	90	40	18	14.5	17	4	24
M26 × 1.5		T7309859	22	90	40	18	14.5	17	4	24.5
M26 × 1.0		T7309N59	18	90	40	18	14.5	17	4	25
M27 × 2.0		T7309879	22	90	40	20	16	19	4	25
M27 × 1.5		T7309889	22	90	40	20	16	19	4	25.5
M27 × 1.0		T7309899	18	90	40	20	16	19	4	26
M28 × 2.0		T7309909	22	90	40	20	16	19	4	26
M28 × 1.5		T7309919	22	90	40	20	16	19	4	26.5
M30 × 2.0		T7309969	22	90	40	22	18	21	4	28
M30 × 1.5		T7309979	22	90	40	22	18	21	4	28.5
M30 × 1.0		T7309989	18	90	40	22	18	21	4	29

ISO

Material Description

VDI 3323

HRC

HB

Recommended

Non-alloy steel

Low alloy steel

High alloyed steel, and tool steel

Stainless steel

Grey cast iron

Nodular cast iron

Malleable cast iron

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

125

190

250

270

300

180

275

300

350

200

325

200

240

180

180

260

3

25

130

230

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

ISO

Material Description

VDI 3323

HRC

HB

Recommended

Aluminum-wrought alloy

Aluminum-cast, alloyed

Copper and Copper Alloys (Bronze / Brass)

Non Metallic Materials

Heat Resistant Super Alloys

Titanium Alloys

Hardened steel

Chilled Cast Iron

Hardened Cast Iron

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

60

100

75

90

130

110

90

100

200

280

250

350

320

400Rm

1050Rm

550

630

400

550

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

YG-1 CO., LTD.

CARBIDE

HSS

YG TAP GENERAL

T7363 SERIES

UNC

Unified coarse threads

Unified Grobgewinde

UNC

Unificato passo grosso

Sets of taps
Gewindebohrer-Satz

This tap is a serial hand tap in set, First, Second and Bottoming.

Bottoming tap of set has final internal thread dimensions only.

Dies ist ein Handgewindebohrer im Satz mit Vor-, Mittel- und Fertigschneider.

Nur der Fertigschneider kann das gewünschte Gewinde schneiden.

First

Second

Bottoming

Hole type

2.0×D

60°

P

Ø d1

ØD2

ØD1

L1

L2

L3

KI

60°

P

Ø d1

Material groups

GS

HSS

DIN 351

2B

60°

I/II/III

Bright

p.B309

Recommended ToolHolder

Plain Shank
TAPPING ER CHUCK
TAPPING CHUCK
ONE STEP TAPPING CHUCK

Unit : mm

SIZE	TPI	EDP No.	Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
ØD1		Bright	L1	L2	L3	ØD2	K	KI	Z	Ød1
#2 - 56UNC		T7363089	9	36	13	2.8	2.1	5	3	1.8
#3 - 48UNC		T7363129	10	40	15	2.8	2.1	5	3	2.1
#4 - 40UNC		T7363169	10	42	18	3.5	2.7	6	3	2.3
#5 - 40UNC		T7363209	10	42	18	3.5	2.7	6	3	2.6
#6 - 32UNC		T7363249	11	45	18	4	3	6	3	2.85
#8 - 32UNC		T7363289	12	48	23	4.5	3.4	6	3	3.5
#10 - 24UNC		T7363329	14	52	26	6	4.9	6	3	3.9
#12 - 24UNC		T7363369	16	56	27	6	4.9	8	3	4.5
1/4 - 20UNC		T7363409	16	56	27	6	4.9	8	3	5.2
5/16 - 18UNC		T7363449	20	63	34	6	4.9	8	3	6.6
3/8 - 16UNC		T7363489	22	70	38	7	5.5	8	4	8
7/16 - 14UNC		T7363529	22	70	38	8	6.2	9	4	9.4
1/2 - 13UNC		T7363569	25	80	45	9	7	10	4	10.75
9/16 - 12UNC		T7363609	26	80	45	11	9	12	4	12.25
5/8 - 11UNC		T7363649	27	90	55	12	9	12	4	13.5
3/4 - 10UNC		T7363709	32	105	65	14	11	14	4	16.5
7/8 - 9UNC		T7363749	32	110	69	18	14.5	17	4	19.5
1 - 8UNC		T7363789	36	110	69	20	16	19	4	22.25
1-1/8 - 7UNC		T7363829	40	125	77	22	18	21	4	25
1-1/4 - 7UNC		T7363869	40	125	77	25	20	23	4	28.25
1-1/8 - 6UNC		T7363909	50	150	88	28	22	25	4	30.75
1-1/2 - 6UNC		T7363949	50	150	88	32	24	27	4	34
1-3/4 - 5UNC		T7363B89	58	160	93	36	29	32	4	39.5
2 - 4½UNC		T7363D29	65	180	102	40	32	35	4	45.25

ISO

Material Description

VDI 3323

HRC

HB

Recommended

Non-alloy steel

Low alloy steel

High alloyed steel, and tool steel

Stainless steel

Grey cast iron

Nodular cast iron

Malleable cast iron

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

125

190

250

270

300

180

275

300

350

200

325

200

240

180

180

260

3

25

130

230

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

ISO

Material Description

VDI 3323

HRC

HB

Recommended

Aluminum-wrought alloy

Aluminum-cast, alloyed

Copper and Copper Alloys (Bronze / Brass)

Non Metallic Materials

Heat Resistant Super Alloys

Titanium Alloys

Hardened steel

Chilled Cast Iron

Hardened Cast Iron

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

60

100

75

90

130

110

90

100

200

280

250

350

320

400Rm

1050Rm

550

630

400

550

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

YG-1 CO., LTD.

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

B303

CARBIDE

HSS

YG TAP GENERAL

T7363 SERIES

UNC

Unified coarse threads

Unified Grobgewinde

UNC

Unificato passo grosso

Sets of taps
Gewindebohrer-Satz

This tap is a serial hand tap in set, First, Second and Bottoming.

Bottoming tap of set has final internal thread dimensions only.

Dies ist ein Handgewindebohrer im Satz mit Vor-, Mittel- und Fertigschneider.

Nur der Fertigschneider kann das gewünschte Gewinde schneiden.

First

Second

Bottoming

Hole type

2.0×D

60°

P

Ø d1

ØD2

ØD1

L1

L2

L3

KI

60°

P

Ø d1

Material groups

GS

HSS

DIN 351

2B

60°

I/II/III

Bright

p.B309

Recommended ToolHolder

Plain Shank
TAPPING ER CHUCK
TAPPING CHUCK
ONE STEP TAPPING CHUCK

Unit : mm

SIZE	TPI	EDP No.	Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
ØD1		Bright	L1	L2	L3	ØD2	K	KI	Z	Ød1
#2 - 56UNC		T7363089	9	36	13	2.8	2.1	5	3	1.8
#3 - 48UNC		T7363129	10	40	15	2.8	2.1	5	3	2.1
#4 - 40UNC		T7363169	10	42	18	3.5	2.7	6	3	2.3
#5 - 40UNC		T7363209	10	42	18	3.5	2.7	6	3	2.6
#6 - 32UNC		T7363249	11	45	18	4	3	6	3	2.85
#8 - 32UNC		T7363289	12	48	23	4.5	3.4	6	3	3.5
#10 - 24UNC		T7363329	14	52	26	6	4.9	6	3	3.9
#12 - 24UNC		T7363369	16	56	27	6	4.9	8	3	4.5
1/4 - 20UNC		T7363409	16	56	27	6	4.9	8	3	5.2
5/16 - 18UNC		T7363449	20	63	34	6	4.9	8	3	6.6
3/8 - 16UNC		T7363489	22	70	38	7	5.5	8	4	8
7/16 - 14UNC		T7363529	22	70	38	8	6.2	9	4	9.4
1/2 - 13UNC		T7363569	25	80	45	9	7	10	4	10.75
9/16 - 12UNC		T7363609	26	80	45	11	9	12	4	12.25
5/8 - 11UNC		T7363649	27	90	55	12	9	12	4	13.5
3/4 - 10UNC		T7363709	32	105	65	14	11	14	4	16.5
7/8 - 9UNC		T7363749	32	110	69	18	14.5	17	4	19.5
1 - 8UNC		T7363789	36	110	69	20	16	19	4	22.25
1-1/8 - 7UNC		T7363829	40	125	77	22	18	21	4	25
1-1/4 - 7UNC		T7363869	40	125	77	25	20	23	4	28.25
1-1/8 - 6UNC		T7363909	50	150	88	28	22	25	4	30.75
1-1/2 - 6UNC		T7363949	50	150	88	32	24	27	4	34
1-3/4 - 5UNC		T7363B89	58	160	93	36	29	32	4	39.5
2 - 4½UNC		T7363D29	65	180	102	40	32	35	4	45.25

ISO

Material Description

VDI 3323

HRC

HB

Recommended

Non-alloy steel

Low alloy steel

High alloyed steel, and tool steel

Stainless steel

Grey cast iron

Nodular cast iron

Malleable cast iron

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

125

190

250

270

300

180

275

300

350

200

325

200

240

180

180

260

3

25

130

230

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

○

ISO

Material Description

VDI 3323

HRC

HB

Recommended

Aluminum-wrought alloy

Aluminum-cast, alloyed

Copper and Copper Alloys (Bronze / Brass)

Non Metallic Materials

Heat Resistant Super Alloys

Titanium Alloys

Hardened steel

Chilled Cast Iron

Hardened Cast Iron

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

60

100

75

90

130

110

90

100

200

280

250

350

320

400Rm

1050Rm

550

630

400

550

CARBIDE

HSS

YG TAP GENERAL

T7509 SERIES

UNF

Unified fine threads

Unified Feingewinde

UNF

Unificato passo fine

Sets of taps
Gewindebohrer-Satz

This tap is a serial hand tap in set, First and Bottoming.

Bottoming tap of set has final internal thread dimensions only.

Handgewindebohrersatz mit Vor- und Fertigschneider.

Nur der Fertigschneider kann das gewünschte Gewinde schneiden.

First

Bottoming

Hole type

2.0×D

60°

P

ØD1

ØD2

L1

L2

L3

KI

Ød1

Material groups

GS

HSS

DIN 2181

2B

60°

I/III

Bright

p.B309

Recommended ToolHolder

Plain Shank

TAPPING ER CHUCK

TAPPING CHUCK

ONE STEP TAPPING CHUCK

Unit : mm

SIZE	TPI	EDP No.	Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
ØD1		Bright	L1	L2	L3	ØD2	K	KI	Z	Ød1
#4	- 48 UNF	T7509189	10	42	18	3.5	2.7	6	3	2.4
#5	- 44 UNF	T7509229	10	42	18	3.5	2.7	6	3	2.7
#6	- 40 UNF	T7509269	11	45	18	4	3	6	3	3
#8	- 36 UNF	T7509309	12	48	23	4.5	3.4	6	3	3.5
#10	- 32 UNF	T7509349	14	52	22	6	4.9	8	3	4.1
#12	- 28 UNF	T7509389	16	56	24	6	4.9	8	3	4.7
1/4	- 28 UNF	T7509429	16	56	24	6	4.9	8	3	5.5
5/16	- 24 UNF	T7509469	17	63	27	6	4.9	8	3	6.9
3/8	- 24 UNF	T7509509	18	63	27	7	5.5	8	4	8.5
7/16	- 20 UNF	T7509549	20	70	32	8	6.2	9	4	9.9
1/2	- 20 UNF	T7509589	20	70	32	9	7	10	4	11.5
9/16	- 18 UNF	T7509629	20	70	32	11	9	12	4	12.9
5/8	- 18 UNF	T7509669	20	70	32	12	9	12	4	14.5
3/4	- 16 UNF	T7509729	22	80	38	14	11	14	4	17.5
7/8	- 14 UNF	T7509769	22	80	38	18	14.5	17	4	20.5
1	- 12 UNF	T7509809	22	90	40	18	14.5	17	4	23.25
1-1/8	- 12 UNF	T7509849	22	90	40	22	18	21	4	26.5

© : Excellent ○ : Good

ISO	P										M					K				
Material Description	Non-alloy steel					Low alloy steel					High alloyed steel, and tool steel					Stainless steel				
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
HRc	125	13	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25	21	
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommended	○	○	○	○	○	○	○										○	○		

ISO	N										S					H				
Material Description	Aluminum-wrought alloy					Aluminum-cast, alloyed					Copper and Copper Alloys (Bronze / Brass)					Non Metallic Materials				
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
HRc	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400Rm	1050Rm	550	630	400
Recommended					○	○	○													

B304

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

YG-1 CO., LTD.

CARBIDE

HSS

YG TAP GENERAL

T7609 SERIES

BSW

Whitworth threads

Whitworth Gewinde

BSW

Filettatura Whitworth

Sets of taps
Gewindebohrer-Satz

This tap is a serial hand tap in set, First, Second and Bottoming.

Bottoming tap of set has final internal thread dimensions only.

Dies ist ein Handgewindebohrer im Satz mit Vor-, Mittel- und Fertigschneider.

Nur der Fertigschneider kann das gewünschte Gewinde schneiden.

First

Second

Bottoming

Hole type

2.0×D

55°

P

ØD1

ØD2

L1

L2

L3

KI

Ød1

Material groups

GS

HSS

DIN 351

55°

I/II/III

Bright

p.B309

Recommended ToolHolder

Plain Shank

TAPPING ER CHUCK

TAPPING CHUCK

ONE STEP TAPPING CHUCK

Unit : mm

SIZE	TPI	EDP No.	Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
ØD1		Bright	L1	L2	L3	ØD2	K	KI	Z	Ød1
W3/32	- 48	T7609129	10	40	15	2.8	2.1	5	3	1.8
W1/8	- 40	T7609209	10	42	18	3.5	2.7	6	3	2.5
W5/32	- 32	T7609289	12	48	23	4.5	3.4	6	3	3.1
W3/16	- 24	T7609329	14	52	26	6	4.9	8	3	3.6
W7/32	- 24	T7609369	16	56	27	6	4.9	8	3	4.4
W1/4	- 20	T7609409	16	56	27	6	4.9	8	3	5.1
W5/16	- 18	T7609449	20	63	34	6	4.9	8	3	6.5
W3/8	- 16	T7609489	22	70	38	7	5.5	8	4	7.9
W7/16	- 14	T7609529	22	70	38	8	6.2	9	4	9.3
W1/2	- 12	T7609569	25	80	45	9	7	10	4	10.5
W9/16	- 12	T7609609	26	80	45	11	9	12	4	12
W5/8	- 11	T7609649	27	90	55	12	9	12	4	13.5
W3/4	- 10	T7609709	32	105	65	14	11	14	4	16.5
W7/8	- 9	T7609749	32	110	69	18	14.5	17	4	19.25
W1	- 8	T7609789	36	110	69	20	16	19	4	22
W1-1/8	- 7	T7609829	40	125	77	22	18	21	4	24.75
W1-1/4	- 7	T7609869	40	125	77	25	20	23	4	27.75
W1-3/8	- 6	T7609909	50	150	88	28	22	25	4	30.5
W1-1/2	- 6	T7609949	50	150	88	32	24	27	4	33.5
W1-5/8	- 5	T7609989	56	150	88	32	24	27	4	35.5
W1-3/4	- 5	T7609989	58	160	93	36	29	32	4	39
W1-7/8	- 4½	T7609989	65	180	102	36	29	32	4	41.5
W2	- 4½	T7609989	65	180	102	40	32	35	4	44.5

© : Excellent ○ : Good

ISO	P										M					K				
Material Description	Non-alloy steel					Low alloy steel					High alloyed steel, and tool steel					Stainless steel				
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
HRc	125	13	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25	21	
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommended	○	○	○	○	○	○	○										○	○		

ISO	N										S					H				
Material Description	Aluminum-wrought alloy					Aluminum-cast, alloyed					Copper and Copper Alloys (Bronze / Brass)					Non Metallic Materials				
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
HRc	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400Rm	1050Rm	550	630	400
Recommended					○	○	○													

B305

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

YG-1 CO., LTD.

CARBIDE

HSS

YG TAP GENERAL

T7343

SERIES

M-LH

ISO metric coarse threads DIN 13

Metrisches ISO-Gewinde DIN 13

ISO MÉTRIQUE DIN13

ISO Metrico passo grosso DIN 13

Sets of taps
Gewindebohrer-Satz

This tap is a serial hand tap in set, First, Second and Bottoming.

Bottoming tap of set has final internal thread dimensions only.

Dies ist ein Handgewindebohrer im Satz mit Vor-, Mittel- und Fertigschneider.

Nur der Fertigschneider kann das gewünschte Gewinde schneiden.

First

Second

Bottoming

Hole type

2.0×D

60°

P

ØD1

ØD2

L1

L2

L3

KI

60°

P

Ød1

Material groups

GS

HSS

DIN 352

6H

60°

I/II/III

Bright

p.B309

Plain Shank

TAPPING ER CHUCK

TAPPING CHUCK

ONE STEP TAPPING CHUCK

Unit : mm

SIZE	Pitch	EDP No.	Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
ØD1	P	Bright	L1	L2	L3	ØD2	K	KI	Z	Ød1
M3	× 0.5	T7343209	11	40	18	3.5	2.7	6	3	2.5
M3.5	× 0.6	T7343229	13	45	21	4	3	6	3	2.9
M4	× 0.7	T7343249	13	45	21	4.5	3.4	6	3	3.3
M4.5	× 0.75	T7343269	16	50	25	6	4.9	8	3	3.7
M5	× 0.8	T7343289	16	52	26	6	4.9	8	3	4.2
M6	× 1.0	T7343319	18	56	27	6	4.9	8	3	5
M8	× 1.25	T7343369	20	63	34	6	4.9	8	3	6.8
M10	× 1.5	T7343429	22	70	38	7	5.5	8	4	8.5
M12	× 1.75	T7343509	24	80	45	9	7	10	4	10.2
M14	× 2.0	T7343549	26	80	45	11	9	12	4	12
M16	× 2.0	T7343609	27	80	45	12	9	12	4	14
M18	× 2.5	T7343659	30	95	58	14	11	14	4	15.5
M20	× 2.5	T7343709	32	95	58	16	12	15	4	17.5
M22	× 2.5	T7343749	32	100	62	18	14.5	17	4	19.5
M24	× 3.0	T7343789	34	110	69	18	14.5	17	4	21
M27	× 3.0	T7343869	36	110	69	20	16	19	4	24
M30	× 3.5	T7343949	40	125	77	22	18	21	4	26.5

► LH=Left hand thread

ISO

Material Description

VDI 3323

HRc

HB

Recommended

P										M				K					
Non-alloy steel					Low alloy steel					High alloyed steel, and tool steel	Stainless steel			Grey cast iron	Nodular cast iron			Malleable cast iron	
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
125	13	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25	21	
	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
○	○	○	○		○	○										○	○		

ISO

Material Description

VDI 3323

HRc

HB

Recommended

N										S						H			
Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials	Heat Resistant Super Alloys				Titanium Alloys		Hardened steel	Chilled Cast Iron	Hardened Cast Iron		
21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
										15	30	25	38	34			55	60	42
										200	280	250	350	320	400Rm	1050Rm	550	630	400
					○	○	○												

YG-1 CO., LTD.

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

CARBIDE

HSS

YG TAP GENERAL

TB373

SERIES

M

ISO metric coarse threads DIN 13

Metrisches ISO-Gewinde DIN 13

ISO MÉTRIQUE DIN13

ISO Metrico passo grosso DIN 13

Sets of taps
Gewindebohrer-Satz

This tap is a serial hand tap in set, First, Second and Bottoming.

Bottoming tap of set has final internal thread dimensions only.

Dies ist ein Handgewindebohrer im Satz mit Vor-, Mittel- und Fertigschneider.

Nur der Fertigschneider kann das gewünschte Gewinde schneiden.

First

Second

Bottoming

Hole type

2.0×D

60°

P

ØD1

ØD2

L1

L2

L3

KI

60°

P

Ød1

Material groups

GS

HSS-E

DIN 352

6HX

60°

I/II/III

Vap

p.B309

Plain Shank

TAPPING ER CHUCK

TAPPING CHUCK

ONE STEP TAPPING CHUCK

Unit : mm

SIZE	Pitch	EDP No.	Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
ØD1	P	Vap	L1	L2	L3	ØD2	K	KI	Z	Ød1
M3	× 0.5	TB373209	11	40	18	3.5	2.7	6	3	2.5
M3.5	× 0.6	TB373229	13	45	21	4	3	6	3	2.9
M4	× 0.7	TB373249	13	45	21	4.5	3.4	6	3	3.3
M4.5	× 0.75	TB373269	16	50	25	6	4.9	8	3	3.7
M5	× 0.8	TB373289	16	52	26	6	4.9	8	3	4.2
M6	× 1.0	TB373319	18	56	27	6	4.9	8	3	5
M8	× 1.25	TB373369	20	63	34	6	4.9	8	3	6.8
M10	× 1.5	TB373429	22	70	38	7	5.5	8	4	8.5
M12	× 1.75	TB373509	24	80	45	9	7	10	4	10.2
M14	× 2.0	TB373549	26	80	45	11	9	12	4	12
M16	× 2.0	TB373609	27	80	45	12	9	12	4	14
M18	× 2.5	TB373659	30	95	58	14	11	14	4	15.5
M20	× 2.5	TB373709	32	95	58	16	12	15	4	17.5

► First with pilot guide

ISO

Material Description

VDI 3323

HRc

HB

Recommended

P										M				K					
Non-alloy steel					Low alloy steel					High alloyed steel, and tool steel	Stainless steel			Grey cast iron	Nodular cast iron			Malleable cast iron	
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
125	13	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25	21	
	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
○	○	○	○		○	○										○	○		

ISO

Material Description

VDI 3323

HRc

HB

Recommended

N										S						H			
Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials	Heat Resistant Super Alloys				Titanium Alloys		Hardened steel	Chilled Cast Iron	Hardened Cast Iron		
21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
										15	30	25	38	34			55	60	42
										200	280	250	350	320	400Rm	1050Rm	550	630	400
					○	○	○												

YG-1 CO., LTD.

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

B306

B307

CARBIDE

HSS

YG TAP GENERAL

TB373

SERIES

M

ISO metric coarse threads DIN 13

Metrisches ISO-Gewinde DIN 13

ISO MÉTRIQUE DIN13

ISO Metrico passo grosso DIN 13

Sets of taps
Gewindebohrer-Satz

This tap is a serial hand tap in set, First, Second and Bottoming.

Bottoming tap of set has final internal thread dimensions only.

Dies ist ein Handgewindebohrer im Satz mit Vor-, Mittel- und Fertigschneider.

Nur der Fertigschneider kann das gewünschte Gewinde schneiden.

First

Second

Bottoming

Hole type

2.0×D

60°

P

ØD1

ØD2

L1

L2

L3

KI

60°

P

Ød1

Material groups

GS

HSS-E

DIN 352

6HX

60°

I/II/III

Vap

p.B309

Plain Shank

TAPPING ER CHUCK

TAPPING CHUCK

ONE STEP TAPPING CHUCK

Unit : mm

SIZE	Pitch	EDP No.	Thread Length	Overall Length	Neck Length	Shank Diameter	Square Size	Square Length	No. of Flute	Tapping Drill Diameter
ØD1	P	Vap	L1	L2	L3	ØD2	K	KI	Z	Ød1
M3	× 0.5	TB373209	11	40	18	3.5	2.7	6	3	2.5
M3.5	× 0.6	TB373229	13	45	21	4	3	6	3	2.9
M4	× 0.7	TB373249	13	45	21	4.5	3.4	6	3	3.3
M4.5	× 0.75	TB373269	16	50	25	6	4.9	8	3	3.7
M5	× 0.8	TB373289	16	52	26	6	4.9	8	3	4.2
M6	× 1.0	TB373319	18	56	27	6	4.9	8	3	5
M8	× 1.25	TB373369	20	63	34	6	4.9	8	3	6.8
M10	× 1.5	TB373429	22	70	38	7	5.5	8	4	8.5
M12	× 1.75	TB373509	24	80	45	9	7	10	4	10.2
M14	× 2.0	TB373549	26	80	45	11	9	12	4	12
M16	× 2.0	TB373609	27	80	45	12	9	12	4	14
M18	× 2.5	TB373659	30	95	58	14	11	14	4	15.5
M20	× 2.5	TB373709	32	95	58	16	12	15	4	17.5

► First with pilot guide

ISO

Material Description

VDI 3323

HRc

HB

Recommended

P										M				K					
Non-alloy steel					Low alloy steel					High alloyed steel, and tool steel	Stainless steel			Grey cast iron	Nodular cast iron			Malleable cast iron	
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
125	13	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25	21	
	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
○	○	○	○		○	○										○	○		

ISO

Material Description

VDI 3323

HRc

HB

Recommended

N										S						H			
Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials	Heat Resistant Super Alloys				Titanium Alloys		Hardened steel	Chilled Cast Iron	Hardened Cast Iron		
21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
										15	30	25	38	34			55	60	42
										200	280	250	350	320	400Rm	1050Rm	550	630	400
					○	○	○												

YG-1 CO., LTD.

phone:+82-32-526-0909, www.yg1.solutions, E-mail:yg1@yg1.solutions

B306

B307

CARBIDE

HSS

YG TAP GENERAL

TC353 SERIES

M

ISO metric coarse threads DIN 13

Metrisches ISO-Gewinde DIN 13

ISO MÉTRIQUE DIN13

ISO Metrico passo grosso DIN 13

Sets of taps
Gewindebohrer-Satz

This tap is a serial hand tap in set, First, Second and Bottoming.

Bottoming tap of set has final internal thread dimensions only..

Dies ist ein Handgewindebohrer im Satz mit Vor-, Mittel- und Fertigschneider.

Nur der Fertigschneider kann das gewünschte Gewinde schneiden.

First

Second


Bottoming

Hole type

2.0×D



Global Cutting Tool Leader **YG-1**



THREADING